

# DH-PFM320D-EN/BS

12V 2A Power Adapter



## Features

- Easy installation
- With indicator light working
- Support  $-30^{\circ}\text{C} \sim +70^{\circ}\text{C}$  wide-range temperature operation, and the full load efficiency of the power supply can be up to 100% at these temperatures
- Accurate overcurrent, overvoltage protection

## Technical Specifications

Model	DH-PFM320D-EN	DH-PFM320D-BS
<b>Electrical Specificaton</b>		
Input	100~240V, 50/60Hz, 0.6A	
Output	12V, 2A(+7% , -3%)	
<b>Protection/Environmental</b>		
Protection	Surge protection, over temperature protection, over current, voltage load protection	
	ESD: EN61000-4-2 +/-4kV Contact; +/-8kV Air	
	Surge: EN61000-4-5" Combination Wave: Common Mode ±4KV (12 ohms); Differential Mode ±2kV (2 ohms)	
Working temperature	-30~70°C	
Working humidity	<90% RH	
<b>Physical Properties</b>		
Weight	170g	
Dimension(LxWxH)	104mmx45mmx33mm	
Installation mode	Plane installation	
Color	Black	
Input plug	2-pin Euro plug	3-pin British plug
Outgoing cord	AC wire: 50cm, DC wire: 80cm	
DC plug	Φ5.5xΦ2.1x12	
<b>Safety Standards</b>		
Certification	CE, FCC	

## Order Information

Type	Part Number	Description
Power	DH-PFM320D-EN	DC12V 2A Power Adapter _ Dahua brand, European standard
	DH-PFM320D-BS	DC12V 2A Power Adapter _ Dahua brand, British standard
	DH-PFM340-5CH	CCTV distributed power supply _Dahua brand, 5x0.8A, DC12V
	DH-PFM341-9CH	CCTV distributed power supply _Dahua brand, 9x0.55A, DC12V

Dimensions (mm/inch)

