



Fanless Panel PC

15"

15"



The back panel I/O is flexible for customized configuration.



Model Name		15" + 2I385CW	15" + CI770C
Dimension (mm)		384W x 312H x 70.5D mm	384W x 312H x 75.5D mm
Weight		4.2kg	4.2kg
Hard drive		2.5" HDD	2.5" HDD
LCD brand		AUO	AUO
LCD size		15 inch, 4:3	15 inch, 4:3
Max Resolution		XGA 1024 x 768	XGA 1024 x 768
Luminance (cd/m ²)		400	400
Contrast Ratio		700:1	700:1
Viewing Angle (H-V)		60(U), 80(D), 80(R), 80(L)	60(U), 80(D), 80(R), 80(L)
Backlight		LED	LED
Touch Screen		Resistive touch screen	Resistive touch screen
MB		2I385CW	CI770C-AC
CPU		Intel Bay Trail-I E3815 1.46 GHz (Single Core) Intel Bay Trail-I E3845 1.91 GHz (Quad Core)	Intel Mobile Ivy Bridge processor Intel Panther Point (PCH) QM77
Chipset			
Memory	Type / Capacity	E3815 DDR3L 1066MT/s E3845 DDR3L 1333MT/s	DDR3 1333 MT/s, Max up to 16GB
	SO-DIMM	N/A	2
	On board memory	2 / 4 GB	N/A
SSD Storage	CF (CFast)	N/A	Optional
	mSATA	Yes	Yes
	On Board SSD	N/A	Optional
VGA		Yes	YES
DVI / HDMI		N/A	DVI / HDMI
USB		4	Built-in 4 x USB, expand up to 9 x USB
COM		4	Built-in 4 x COM, expand up to 10 x COM
MiniPCle	Slot 1	(Full Size) PCIe/ USB/mSATA	PCIe / USB
	Slot 2	(Half Size) USB/mSATA	PCIe / mSATA / USB
PCI / PCIe		N/A	Built-in 1 x PCI, expand up to 2 x PCI / PCIe
SIM Card Holder		N/A	2
GPIO		4DI/4DO (Optional)	8DI / 8DO (Optional)
Ethernet		2 x Intel GbE	2 x Intel GbE
Audio		Yes	Line-out / Mic-in
Power Input		DC IN+9V~36V	DC IN +12V
Mounting		VESA 75 / 100 & Panel Mount	VESA 75 / 100 & Panel Mount
Panel frame water proof		IP65	IP65
Optional MB		3I525C / 3I847C	N/A
Expansion		3G/4G, GPS, IEEE1394, Bluetooth, WI-FI, Webcam, I/O, PoE	3G/4G, GPS, IEEE1394, Bluetooth, WI-FI, Webcam, I/O, PoE
Operating Temp.		0~50°C for HDD, -20°C~60°C for mSATA / 2.5" SSD HDD	0~50°C for HDD, -20°C~60°C for mSATA / 2.5" SSD HDD
Operating Humidity		5~90% @ 39°C, non-condensing	5~90% @ 39°C, non-condensing